



LB-460-NFSPO Broadband Horn Antenna 0.4-6GHz 10dB Gain N Type Female

Broadband Horn Antenna Operating From 0.4GHz to 6GHz With a Nominal 10dB Gain With N Type Female Connector

Product Information

SKU	LB-460-NFSPO	Patents	ZL201630454765.2 (China)
-----	--------------	---------	--------------------------

Description

Broadband horn antenna LB-460-NFSPO, operating from 0.4 to 6GHz with a nominal 10dB gain and low VSWR 1.5:1 with N Type Female output connector. The model LB-460-NFSPO has uniform gain through its frequency span, providing efficient performance characteristics and directionality. It can handle 500W continuously and 800W peak power. Constructed of lightweight corrosion-resistant aluminum, the horn comes with a specially designed weatherproof radome which provides excellent protection against the rain and dust but has very little loss across the full operating frequency band. This broadband horn antenna is linearly polarized and ideally suited for EMI testing, direction finding, surveillance, antenna gain and pattern measurements and other applications.

Technical Specification


Electrical Specification		Interface	
Frequency, Min (GHz)	0.4	Output Type	Coaxial
Frequency, Max (GHz)	6	Connector	N Type
Gain, Typ (dBi)	10	Connector Gender	Female
Polarization	Linear	Mechanical Specification	
3dB Beamwidth, E-Plane, Min (Deg.)	31	Body Material	Al
3dB Beamwidth, E-Plane, Max (Deg.)	104	Finish	Chemical Conversion Coating, Gray Paint
3dB Beamwidth, H-Plane, Min (Deg.)	35	Size, W (mm)	532
3dB Beamwidth, H-Plane, Max (Deg.)	94	Size, H (mm)	340
Cross Pol. Isolation, Typ (dB)	25	Size, L (mm)	443
VSWR, Typ	1.5:1	Weight, (kg)	9
Impedance, (Ohm)	50		
Power Handling, CW, (W)	500		
Power Handling, Peak, (W)	800		

Additional Information


Application	Outdoor, Waterproof and Dustproof, Fixed	Solution for	Gain Reference Antenna Measurement Reflector Feed Far-field Measurement System Intergration
-------------	--	--------------	---

Outline Drawing

N-Female Output with Radome (Option, P/N: LB-460-NFSPO, Outdoor Application)




N-Female Output with L Type Mounting Bracket & Radome (Option, P/N: LB-460-L & LB-460- NFSPO, Outdoor Application)




Typical Test Results

Gain






Antenna Factor




Antenna Factor (Table)

Frequency(GHz)	1m		3m		10m	
	Gain(dBi)	AF(dB/m)	Gain(dBi)	AF(dB/m)	Gain(dBi)	AF(dB/m)
0.40	5.42	16.83	5.72	16.53	5.19	17.06
0.50	6.76	17.43	7.61	16.58	7.38	16.81
0.60	7.24	18.54	8.02	17.75	8.13	17.65
0.70	8.35	18.76	9.23	17.88	8.98	18.13
0.80	9.20	19.08	10.09	18.18	9.91	18.36
0.90	9.17	20.13	10.26	19.04	10.13	19.16
1.00	8.59	21.62	9.57	20.64	9.78	20.43
2.00	8.83	27.40	10.69	25.55	11.32	24.91
3.00	8.68	31.07	10.80	28.95	11.71	28.04
4.00	9.99	32.26	10.75	31.50	10.97	31.28
5.00	11.20	32.99	11.65	32.54	11.99	32.20
6.00	11.91	33.87	12.93	32.84	13.16	32.62


Field Strength




Cross Polarization Isolation










VSWR



Pattern







Related Products



LB-460-L L type mounting bracket



Tripod_50Kg Al Alloy Tripod



Carrying Case_LB-460 Al Alloy Carrying Case



NM-NM-A050-1000 Flexible Cable Assembly 1000mm DC-18GHz N Male to N Male



NM-NM-A050-1500 Flexible Cable Assembly 1500mm DC-18GHz N Male to N Male



NM-NM-A050-2000 Flexible Cable Assembly 2000mm DC-18GHz N Male to N Male



NM-NM-A050-3000 Flexible Cable Assembly 3000mm DC-18GHz N Male to N Male



NM-NM-A050-5000 Flexible Cable Assembly 5000mm DC-18GHz N Male to N Male



NM-NM-A050-10000 Flexible Cable Assembly 10000mm DC-18GHz N Male to N Male



NM-NM-A050-20000 Flexible Cable Assembly 20000mm DC-18GHz N Male to N Male



NM-NM-A100-500 Flexible Cable Assembly 500mm DC-18GHz N Male to N Male



NM-NM-A100-1000 Flexible Cable Assembly 1000mm DC-18GHz N Male to N Male



NM-NM-A100-1500 Flexible Cable Assembly 1500mm DC-18GHz N Male to N Male



NM-NM-A100-2000 Flexible Cable Assembly 2000mm DC-18GHz N Male to N Male



NM-NM-A100-3000 Flexible Cable Assembly 3000mm DC-18GHz N Male to N Male



NM-NM-A100-5000 Flexible Cable Assembly 5000mm DC-18GHz N Male to N Male



NM-NM-A100-10000 Flexible Cable Assembly 10000mm DC-18GHz N Male to N Male



NM-NM-A100-20000 Flexible Cable Assembly 20000mm DC-18GHz N Male to N Male

Similar Products



LB-225-NF Broadband Horn Antenna 0.2-2.5GHz 12dB Gain N Type Female



LB-225-7/16F Broadband Horn Antenna 0.2-2.5GHz 12dB Gain 7/16 DIN Female



LB-460-NF Broadband Horn Antenna 0.4-6.0 GHz 10dB Gain N Type Female



LB-560-NF Broadband Horn Antenna 0.5-6.0 GHz 11dB Gain N Type Female



LB-560-NF SPO Broadband Horn Antenna 0.5-6GHz 11dB Gain N Type Female



LB-660-NF Broadband Horn Antenna 0.6-6.0 GHz 11dB Gain N Type Female



LB-660-NF SPO Broadband Horn Antenna 0.6-6GHz 11dB Gain N Type Female



LB-OSJ-0460-NF Open Boundary Quad-Ridged Dual Polarization Horn Antenna 0.4-6GHz 12dB Gain N Type Female



LB-OSJ-0460-SF Open Boundary Quad-Ridged Dual Polarization Horn Antenna 0.4-6GHz 12dB Gain SMA Female



LB-OSJ-0760-NF Open Boundary Quad-Ridged Dual Polarization Horn Antenna 0.7-6GHz 11dB Gain N Type Female



LB-OSJ-0760-SF Open Boundary Quad-Ridged Dual Polarization Horn Antenna 0.7-6GHz 11dB Gain SMA Female

About this Datasheet

<ul style="list-style-type: none"> • Product Information Product Link: https://www.ainfoinc.com/lb-460-nfspo-broadband-horn-antenna-0-4-6-ghz-10db-gain-n-type-female Data subject to change without notice. © A-INFO INC. 2024. All Rights Reserved 	<ul style="list-style-type: none"> • Contact Us Address: 60 Tesla, Irvine, CA 92618, USA Website: www.ainfoinc.com Email: sales@ainfoinc.com 	<ul style="list-style-type: none"> • Phone & Fax Phone: +1-949-639-9688 +1-949-639-9608 Fax: +1-949-639-9670
---	--	--